



Alarm Exit Hardware

MP-9000-ARS-28/36/48 Panic Rim Exit Device
MP-9000-ARF-28/36/48 Fire Rim Exit Device



CONFORMS TO STANDARDS
UL 10C AND UBC 7-2 (1997)



MP-9000-ARF-36-US32D

9000 series Rim Type Exit Devices c/w battery operated alarm

Alarm unit has an internal horn. When the push rail is depressed, the horn sounds to provide audible an means of signaling that the door has been opened and violated.

The unit has changeable 2 minute alarm cutoff or manual reset. Preset at factory for 2 minute alarm cut off.

Jumper cable is provided to switch to continuous alarm.

The key switch to turn the alarm off is a standard 1 1/4" cylinder . The alarm operates on one standard 9 volt transistor battery, when battery is weak the horn will emit an intermittent signal.

Alarmed units are supplied with two switches. One switch monitors the push rail and the other switch monitors the latchbolt for full proof security.

Unit includes "emergency exit only. Alarm will sound" decal for application on door or unit with Chinese version.

For Single leave door

MP-9000-ARS-36 Alarm rim type 36" door (panic grade)

MP-9000-ARS-48 Alarm rim type 48" door (panic grade)

MP-9000-ARF-36 Alarm rim type 36" door (fire grade)

MP-9000-ARF-48 Alarm rim type 48" door (fire grade)

For Double leaves door

MP-9000-ARS-28 Alarm rim type 28" door (Panic grade)

MP-9000-ARF-28 Alarm rim type 28" door (Fire grade)

To be combined with 9000 series vertical rod

MP-9000-AVS-28 Alarm vertical rod 28" door (Panic grade)

MP-9000-AVF-28 Alarm vertical rod 28" door (Fire grade)

From outside to be operated by:

Rim cylinder


Pull handle on plate

Tubular lever / knob with various function

Clutch free wheeling bolt thru escutcheon trim

Thumb-piece trim

Single door



Double door

